

Appl. No. 10/743,242
Resp. dated June 13, 2006
Reply to Office Action of Apr. 13, 2005

RECEIVED
CENTRAL FAX CENTER
JUN 13 2006

Amendments to the Claims:

Although none of the currently pending claims are being amended in this Response, Applicants include this listing of claims for the Examiner's convenience. This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (previously presented) A composite elastic material having a first direction and a second direction, the second direction being perpendicular to the first direction, at least a portion of the composite elastic material comprising:

a gatherable nonwoven layer having a nonwoven bond pattern comprising a plurality of bond elements;

a layer of substantially parallel elastomeric filaments adjacent to a surface of the nonwoven layer; and

a bonding component that joins the elastomeric filaments to the adjacent surface of the nonwoven layer in a face to face configuration;

where the bond elements have a first bond dimension relative to the first direction and a second bond dimension relative to the second direction and where the first bond dimension is greater than the second bond dimension and where the first and second bond dimensions of the bond elements of the nonwoven bond pattern define a nonwoven bond pattern dimension ratio such that the nonwoven bond pattern dimension ratio is greater than 1.

2. (original) The composite elastic material of claim 1, where the elastomeric filaments are parallel to the first direction.

3. (original) The composite elastic material of claim 1, where the elastomeric filaments are parallel to the second direction.

4. (original) The composite elastic material of claim 1, where the bonding component is an adhesive.

5. (original) The composite elastic material of claim 1, where the bonding component is a layer of elastomeric meltblown fibers.

6. (previously presented) The composite elastic material of claim 1, further comprising a second gatherable nonwoven layer having a nonwoven bond pattern comprising a plurality of bond elements where the bond elements have a first bond dimension relative to the first direction and a second bond dimension relative to the second direction and where the first and second bond dimensions of the bond elements of the nonwoven bond pattern define a

Appl. No. 10/743,242
Resp. dated June 13, 2006
Reply to Office Action of Apr. 13, 2005

nonwoven bond pattern dimension ratio such that the nonwoven bond pattern dimension ratio is greater than 1.

7. (original) The composite elastic material of claim 1, further comprising a laminate bond pattern comprising a plurality of laminate bond elements having a first dimension relative to the first direction and a second dimension relative to the second direction and where the first and second dimensions of the laminate bond elements of the laminate bond pattern define a laminate bond pattern dimension ratio.

8. (original) The composite elastic material of claim 7, where the laminate bond pattern dimension ratio is greater than 1.

9. (original) The composite elastic material of claim 7, where the laminate bond pattern dimension ratio is less than 1.

10. (original) The composite elastic material of claim 7 where the laminate bond elements are thermal bonds.

11. (original) The composite elastic material of claim 7 where the laminate bond elements are ultrasonic bonds.

12. (withdrawn) A method of producing the composite elastic material of claim 1, with a first direction and a second direction, the second direction being perpendicular to the first direction, the method comprising the steps of :

- a) providing at least one gatherable nonwoven layer having a nonwoven bond pattern comprising a plurality of bond elements;
- b) providing a layer of substantially parallel elastomeric filaments adjacent to a surface of the facings layer;
- c) providing a bonding component; and
- d) joining the gatherable nonwoven layer to the layer of elastomeric filaments in a face to face configuration;

where the bond elements have a first bond dimension relative to the first direction and a second bond dimension relative to the second direction and where the first and second bond dimensions of the bond elements of the nonwoven bond pattern define a nonwoven bond pattern dimension ratio such that the nonwoven bond pattern dimension ratio is greater than 1.

13. (withdrawn) The method of claim 12, where the elastomeric filaments are parallel to the first direction.

Appl. No. 10/743,242
Resp. dated June 13, 2006
Reply to Office Action of Apr. 13, 2005

14. (withdrawn) The method of claim 12, where the elastomeric filaments are parallel to the second direction.
15. (withdrawn) The method of claim 12, where the bonding component is an adhesive that is applied to the surface of the nonwoven layer.
16. (withdrawn) The method of claim 12, where the bonding component is a layer of elastomeric meltblown fibers that is applied to layer of elastomeric filaments.
17. (withdrawn) The method of claim 12, further comprising the steps of providing a second gatherable nonwoven layer having a nonwoven bond pattern comprising a plurality of bond elements where the bond elements have a first bond dimension relative to the first direction and a second bond dimension relative to the second direction and where the first bond dimension is greater than the second bond dimension and where the nonwoven bond pattern dimension ratio is greater than 1.
18. (withdrawn) The method of claim 17, where the joining of the nonwoven facing layer to the elastomeric filaments and the elastomeric filaments to the second nonwoven facing layer occurs by passing the composite elastic material into a nip formed between an anvil calender roller and a bonding calender roller.
19. (withdrawn) The method of claim 18, where the bonding calender roller is a point unbonded calender roller.
20. (withdrawn) The method of claim 18, where the bonding calender roller is a smooth calender roller.
21. (withdrawn) The method of claim 12, further comprising the step of bonding the composite elastic material with a laminate bond pattern comprising a plurality of laminate bond elements having a first dimension relative to the first direction and a second dimension relative to the second direction and where the first and second dimensions of the laminate bond elements of the laminate bond pattern define a laminate bond pattern dimension ratio.
22. (withdrawn) The method of claim 21, where the laminate bond pattern dimension ratio is greater than 1.
23. (withdrawn) The method of claim 21, where the laminate bond pattern dimension ratio is less than 1.
24. (withdrawn) The method of claim 21, where the laminate bond elements are thermal bonds.

Appl. No. 10/743,242
Resp. dated June 13, 2006
Reply to Office Action of Apr. 13, 2005

25. (withdrawn) The method of claim 21, where the laminate bond elements are ultrasonic bonds.